


SRH



PRODUCT DESCRIPTION

The SRHH Self-Regulating Heating Cable is designed for freeze protection and high process temperature maintenance of metal and non-metal pipes, vessels, and equipment where steam cleaning is required. CANSTAL SRH cable is certified to be used in nonhazardous and hazardous areas. CANSTAL SRH cable can maintain Temperatures up 300°F(150°C) and intermittent exposure temperature of 482°F(250°C).

PRODUCT STRUCTURE



Ordering Information

SRH(a)-b

a = Output Wattage, 5, 10, 15, 20 W/ft
 SRH = Model Name
 b = Voltage, 1 = 100-120V , 2 = 200-277V

Certification / Approvals



Class I, Division 2, Groups A, B, C, and D T6;
 Class II/III, Division 2, Groups E, F and G T6;
 Class 1 Zone 1 AEx/Ex eb IIC Gb
 Zone 21 AEx/Ex tb IIIC T85°C Db
 Ta = -40°C to +55°C
 Type 4X, IP66



II 2 G Ex 60079-30-1 IIC T6 Gb
 II 2 D Ex 60079-30-1 IIIC T85°C Db
 Ta = -40°C to +55°C
 IP66



Ex 60079-30-1 IIC T6 Gb;
 Ex 60079-30-1 IIIC T85°C Db

Connection Kits


Canstal offers system components for power connections, splice or tee connections and end terminations to ensure proper functioning of the products and comply with warranty and approvals requirements.

For easier installation and safe operation, use of substituted parts are not recommended. Please contact Canstal for more information on system components.

SPECIFICATION

Max. Intermittent Exposure Temp.	482°F (250°C)
Max. Maintain or Continuous Exposure Temp.	300°F (150°C)
Supply Voltage	100-120V or 200-277V
Output Wattage	5, 10, 15, 20W/ft @50°F [16, 33, 49, 66W/m @10°C]
Bus wire	16 AWG
Min. Bending Radius	0.8" @70°F [20mm @20°C], 1.8" @-76°F [45mm @-60°C]
Min. Installation Temperature	-76°F (-60°C)
Min. Start-up Temperature	-40°F (-40°C)
Maximum Circuit Breaker Size	50A (40A for ATEX and IECEx)
Outer Jacket Color	Red
Heating Cable Dimensions (Nominal)	0.50" x 0.20" [13.0mm x 5.0mm]
Heating Cable Weight	0.0902lb/ft [0.134kg/m]

Nominal Power Output Ratings on Insulated Metal Pipes at 120/240



Voltage	Circuit length adjustment factor			
	5SRH-2	10SRH-2	15SRH-2	20SRH-2
208V	0.93	0.94	0.94	0.94
240V	1.00	1.00	1.00	1.00
277V	1.10	1.10	1.11	1.11

Voltage	Power adjustment factor			
	5SRH-2	10SRH-2	15SRH-2	20SRH-2
208V	0.93	0.94	0.94	0.94
240V	1.00	1.00	1.00	1.00
277V	1.10	1.10	1.11	1.11

[Note]

1. Thermal outputs above are tested in accordance with IEC/IEEE 60079-30-1:2015, with each model on a metallic pipe insulated with a fiberglass insulation.
2. The power output will be derated by 25% on plastic pipes. GAT-L164 aluminum tape is required for installation on plastic pipes.



Max. Circuit Length based on Circuit Breaker Selection

Catalog Number	Start-Up Temperature °F (°C)	Maximum Circuit Length per Circuit Breaker, feet (meters)									
		120V					240V				
		15A	20A	30A	40A	50A*	15A	20A	30A	40A	50A*
SRH- (5W/FT)	50 (10)	180 (54)	240 (73)	358 (109)	358 (109)	358 (109)	360 (109)	480 (146)	709 (216)	709 (216)	709 (216)
	0 (-18)	141 (42)	187 (57)	281 (85)	358 (109)	358 (109)	281 (85)	375 (114)	562 (171)	709 (216)	709 (216)
	-20 (-29)	129 (39)	172 (52)	258 (78)	345 (105)	358 (109)	258 (78)	345 (105)	517 (157)	689 (210)	709 (216)
	-40 (-40)	120 (36)	159 (48)	239 (72)	319 (97)	358 (109)	239 (72)	319 (97)	478 (145)	638 (194)	709 (216)
SRH- (10 W/FT)	50 (10)	107 (32)	142 (43)	213 (65)	253 (77)	253 (77)	213 (65)	284 (86)	427 (130)	502 (153)	502 (153)
	0 (-18)	87 (26)	116 (35)	174 (53)	232 (70)	253 (77)	174 (53)	232 (70)	348 (106)	464 (141)	502 (153)
	-20 (-29)	81 (24)	108 (32)	162 (49)	216 (65)	253 (77)	162 (49)	216 (65)	324 (98)	432 (131)	502 (153)
	-40 (-40)	76 (23)	101 (30)	152 (46)	202 (61)	253 (76)	152 (46)	202 (61)	303 (92)	404 (123)	502 (153)
SRH- (15 W/FT)	50 (10)	78 (23)	104 (31)	156 (47)	203 (62)	203 (62)	156 (47)	208 (63)	312 (95)	400 (122)	400 (122)
	0 (-18)	65 (19)	87 (26)	130 (39)	174 (52)	203 (62)	130 (39)	174 (52)	261 (79)	347 (105)	400 (122)
	-20 (-29)	61 (18)	82 (24)	122 (37)	163 (49)	203 (62)	122 (37)	163 (49)	245 (74)	326 (99)	400 (122)
	-40 (-40)	58 (17)	77 (23)	115 (35)	154 (46)	192 (58)	115 (35)	154 (46)	230 (70)	307 (93)	384 (117)
SRH- (20 W/FT)	50 (10)	58 (17)	78 (23)	117 (35)	155 (47)	174 (53)	117 (35)	155 (47)	233 (71)	311 (94)	348 (106)
	0 (-18)	50 (15)	67 (20)	100 (30)	134 (40)	167 (50)	100 (30)	134 (40)	200 (61)	267 (81)	334 (101)
	-20 (-29)	47 (14)	63 (19)	95 (28)	126 (38)	158 (48)	95 (28)	126 (38)	190 (57)	253 (77)	316 (96)
	-40 (-40)	45 (13)	60 (18)	90 (27)	120 (36)	150 (45)	90 (27)	120 (36)	180 (54)	240 (73)	300 (91)

* 50A Circuit Breaker Size is not applicable for ATEX/IECEx.

[Note]

1. The circuit lengths are based on trip current characteristics of Type QO and Type QCB devices. For devices with different trip characteristics please consult Canstal's team.
2. Use local electrical codes to select appropriate branch circuit breakers.
3. The total length of heating cables connected to the circuit breaker is the sum of all cables that have been spliced or interconnected in parallel. Ensure that the total length does not exceed the maximum circuit length as indicated above.
4. Ground fault protection of equipment is required for heat tracing branch circuits with typical trip level of 30mA. Thermal magnetic breakers are recommended to reduce nuisance tripping.
5. It is recommended to start up the circuits at higher temperatures, when possible, to avoid large start-up or in-rush current which may trip the circuit breaker.